


## YDEEVNEDEKLARATION

Nr: 204

1	Entydig identifikationskode for produkttypen:																								
	<ul style="list-style-type: none"> <li>• FLÜGGER Floor Paint Epoxy og PU</li> <li>• + Varenummer og batchnummer på pakken</li> </ul>																								
2	Tilsligtet anvendelse:																								
	<ul style="list-style-type: none"> <li>• EN-1504-2 Maling til mineralske underlag</li> </ul>																								
3	Fabrikant:																								
	<ul style="list-style-type: none"> <li>• FLÜGGER Grönkullen SE-517 81 Bollebygd. www.flugger.se</li> </ul>																								
4	Vurdering og kontrol af ydeevnets konstans (AVCP-system):																								
	<ul style="list-style-type: none"> <li>• System 3</li> </ul>																								
5	Harmoniseret standard:																								
	<ul style="list-style-type: none"> <li>• EN 1504-2:2004 Products and systems for the protection and repair of concrete structures. Part 2: Surface protection systems for concrete</li> <li>• SP 0402</li> </ul>																								
6	Deklareret ydeevne:																								
	<table border="1"> <thead> <tr> <th>Flügger Floor Paint</th> <th>Epoxy</th> <th>PU</th> </tr> </thead> <tbody> <tr> <td>Reaction to fire</td> <td>B-s1</td> <td>Bfl-s1</td> </tr> <tr> <td>Permeability to water vapour</td> <td>Class 1</td> <td>Class 1</td> </tr> <tr> <td>Capillary absorption and permeability to water</td> <td>W&lt; 0,1 kg/m<sup>2</sup> h 0,5</td> <td>W&lt; 0,1 kg/m<sup>2</sup> h 0,5</td> </tr> <tr> <td>Adhesion strength by pull off test</td> <td>&gt;2,0 N/mm<sup>2</sup></td> <td>&gt;2,0 N/mm<sup>2</sup></td> </tr> <tr> <td>Abrasion resistance</td> <td>&lt;3000 mg</td> <td></td> </tr> <tr> <td>Resistance to severe chemical attack</td> <td>Class 1</td> <td></td> </tr> <tr> <td>Impact resistance</td> <td>Class 1</td> <td></td> </tr> </tbody> </table>	Flügger Floor Paint	Epoxy	PU	Reaction to fire	B-s1	Bfl-s1	Permeability to water vapour	Class 1	Class 1	Capillary absorption and permeability to water	W< 0,1 kg/m <sup>2</sup> h 0,5	W< 0,1 kg/m <sup>2</sup> h 0,5	Adhesion strength by pull off test	>2,0 N/mm <sup>2</sup>	>2,0 N/mm <sup>2</sup>	Abrasion resistance	<3000 mg		Resistance to severe chemical attack	Class 1		Impact resistance	Class 1	
Flügger Floor Paint	Epoxy	PU																							
Reaction to fire	B-s1	Bfl-s1																							
Permeability to water vapour	Class 1	Class 1																							
Capillary absorption and permeability to water	W< 0,1 kg/m <sup>2</sup> h 0,5	W< 0,1 kg/m <sup>2</sup> h 0,5																							
Adhesion strength by pull off test	>2,0 N/mm <sup>2</sup>	>2,0 N/mm <sup>2</sup>																							
Abrasion resistance	<3000 mg																								
Resistance to severe chemical attack	Class 1																								
Impact resistance	Class 1																								
7	Ydeevnen for det ovenfor anførte produkt er i overensstemmelse med den deklarerede ydeevne. Denne ydeevnedeklaration udstedes i overensstemmelse med forordning (EU) nr. 305/2011 på eneansvar af den ovenfor anførte fabrikant. Underskrevet for fabrikanten og på vegne af denne af:																								
	<p>Navn:</p> <ul style="list-style-type: none"> <li>• <b>Anders Frisk</b></li> </ul> <p>Stilling:</p> <ul style="list-style-type: none"> <li>• <b>Regulatory Affairs Specialist</b></li> </ul> <p>Sted:</p> <ul style="list-style-type: none"> <li>• <b>Bollebygd</b></li> </ul> <p>Dato: 2018-08-14</p> <p>•</p> <p>Signature: </p>																								